

Appln. Serial No. 09/881,604  
Amendment Dated August 15, 2007  
Reply to Office Action Mailed May 17, 2007

RECEIVED  
CENTRAL FAX CENTER

AUG 15 2007

AMENDMENTS TO THE CLAIMS

This listing of claims replaces all prior versions, and listings, of claims in the application:

1           1.       (Previously Presented) A method of dynamically protecting access to a first  
2 network, comprising:  
3               receiving, in a system, a data unit containing a source address indicating a source  
4 of a data unit;  
5               matching the source address with information stored in the system;  
6               enabling entry of the data unit to the first network for communication to a  
7 destination device on the first network if the source address matches the information stored in the  
8 system and denying entry of the data unit to the first network if the source address does not  
9 match the information stored in the system,  
10              wherein the destination device is separate from the system;  
11              determining whether the data unit contains an identifier of a codec type that  
12 matches a stored codec type; and  
13              indicating occurrence of an attack of the first network in response to determining  
14 that the identifier is of a codec type that does not match the stored codec type.

1           2.       (Original) The method of claim 1, wherein matching the source address with the  
2 information comprises matching the source address with one or more entries of a network  
3 address translation mapping table.

1           3.       (Original) The method of claim 1, wherein matching the source address  
2 comprises matching an Internet Protocol address.

1           4.       (Cancelled)

Appl. Serial No. 09/881,604  
Amendment Dated August 15, 2007  
Reply to Office Action Mailed May 17, 2007

1           5.     (Previously Presented) A method of dynamically protecting access to a first  
2 network, comprising:  
3                 receiving, in a system, a data unit containing a source address indicating a source  
4 of the data unit;  
5                 matching, by an address filter in the system, the source address with information  
6 stored in the system;  
7                 enabling, by the address filter, entry of the data unit to the first network if the  
8 source address matches the information stored in the system and denying entry of the data unit to  
9 the first network if the source address does not match the information stored in the system; and  
10                determining, by a protocol filter, if the data unit contains a payload according to a  
11 predetermined protocol, and denying, by the protocol filter, entry of the data unit if the data unit  
12 does not contain the payload according to the predetermined protocol.

1           6.     (Original) The method of claim 5, wherein determining if the data unit contains a  
2 payload according to the predetermined protocol comprises determining if the data unit contains  
3 a payload according to a Real-Time Protocol or Real-Time Control Protocol.

1           7.     (Previously Presented) A method of dynamically protecting access to a first  
2 network, comprising:  
3                 receiving, in a system, a data unit containing a source address indicating a source  
4 of a data unit;  
5                 matching the source address with information stored in the system;  
6                 enabling entry of the data unit to the first network if the source address matches  
7 the information stored in the system and denying entry of the data unit to the first network if the  
8 source address does not match the information stored in the system; and  
9                 storing profile information for a telephony call session, and determining if an  
10 unauthorized access of the first network is occurring based on the profile information.

Appln. Serial No. 09/881,604  
Amendment Dated August 15, 2007  
Reply to Office Action Mailed May 17, 2007

1           8.       (Original) The method of claim 7, wherein storing the profile information  
2 comprises storing a threshold representing a maximum acceptable rate of incoming data units  
3 from an external network to the first network.

1           9.       (Original) The method of claim 8, further comprising calculating a value for the  
2 threshold based on a frame size used in the call session.

1           10.      (Original) The method of claim 8, wherein storing the profile information further  
2 comprises storing a pattern expected in incoming data units.

1           11.      (Original) The method of claim 10, wherein storing the pattern comprises storing  
2 a codec type used in the call session.

1           12.      (Original) The method of claim 8, further comprising generating an alarm if the  
2 system detects a rate of incoming data units from the external network to the first network  
3 exceeding the threshold.

1           13.      (Original) The method of claim 8, further comprising denying further transport of  
2 incoming data units from the external network to the first network for the call session if the  
3 system detects a rate of incoming data units from the external network to the first network  
4 exceeding the threshold.

1           14. – 18. (Cancelled)

Appin. Serial No. 09/881,604  
Amendment Dated August 15, 2007  
Reply to Office Action Mailed May 17, 2007

1           19.   (Currently Amended) An article comprising at least one computer-readable  
2 storage medium containing instructions for protecting a first network, the instructions when  
3 executed causing a system to:  
4               determine if a rate of incoming data units from an external network to the first  
5 network exceeds a predetermined threshold;  
6               perform a security action if the determined rate of incoming data units exceeds the  
7 predetermined threshold; and  
8               determine if each incoming packet has a predetermined pattern,  
9               wherein the instructions when executed cause the system to determine if each  
10 incoming packet has the predetermined pattern by checking if each incoming packet has an  
11 indication of a predetermined codec type.

1           20. - 24. (Cancelled)

1           25.   (Previously Presented) A system for use in communications between a first  
2 network and an external network, comprising:  
3               a storage module to store a threshold value for a communications session, the  
4 threshold value representing an acceptable rate of incoming data units from the external network  
5 to the first network; and  
6               a controller adapted to deny further entry of data units from the external network  
7 to the first network in the communications session in response to the controller detecting that the  
8 rate of incoming data units exceeds the threshold value,  
9               the storage module to further store a codec type for the communications session,  
10 wherein the controller is adapted to deny entry of an incoming data unit if the incoming data unit  
11 does not contain an indication of the codec type.

1           26.   (Cancelled)